



**8300
SERIES**

8300 SERIES

Heavy-Duty Commercial Grade 1 Rim Exit Devices



Standard Features

- **Certification** ANSI A156.3, 1994, Grade 1, UL listed
- **Rail** Fits 28" to 36" doors
- **Latch** Stainless steel 5/8" throw
- **Backset** 2-3/4"
- **Strike** Adjustable with slotted holes for adjustments
- **Fasteners** Accommodates wood or metal doors
- **Door Range** 1-3/4" to 2" thickness
- **Door Preparation** Surface mounted
- **Warranty** 10 year limited

Optional Features

- **Rail** Fits 48" door (special order)
- **Exterior Trim** Exterior blank pull, exterior pull with cylinder cut out, entry ball knob trim, storeroom ball knob trim, entry lever trim without clutch, exterior thumb piece trim, exterior escutcheon lever trim, pull trim with rim cylinder
- **Cylinder*** Schlage (SCC), Schlage C (SC5) 5-pin, Schlage E (SCE), Arrow A (ARA), Corbin 60 (C06), Corbin 59A1 (C059A1), Corbin Russwin L4 (CL4), Russwin D1 (RD1), Sargent LA (SAL), Schlage F (SCF), Weiser E (WRE), Yale 8 (YA8), Yale GA (YGA)
- **Keying** Grand master key (GMK), construction master key (CMK), master key (MK), keyed different (KD), keyed alike (KA), interchangeable core uncombined (IC), 0-bitted (OBIT)
- **UL Listed** 3 hour fire rated device available
- **Fire Rated** UL labeled fire rated device available for use on doors rated up to 3 hours. Fire rated device also available for larger doors up to a maximum of 4' x 8'. Specify when ordering.
- **Strikes** Other strikes available

* All cylinders 6-pin except Schlage C (SC5) - 5-pin.



How To Order 8300 Series

